MANCHESTER•BOSTON REGIONAL AIRPORT PARKING GARAGE: LEVEL-5 FLOOR & LEVEL-4 CEILING SEALANTS, WATERPROOFING, & MISCELLANEOUS REPAIRS




One Airport Road, Suite 300
Manchester, New Hampshire 03103
www.flymanchester.com

AECOM

1155 ELM STREET, SUITE 401 MANCHESTER, NH 03101 PROJECT # 60638480_T05

LIST OF DRAWINGS

| SHEET # | DRAWING NO. | <u>TITLE</u> |
|---------|-----------------|--|
| | GENERAL: | |
| 1 | TS.21-1 | TITLE SHEET & AIRPORT SITE PLAN |
| 2 | GN.21-1 | GENERAL NOTES & WORK ITEM LIST |
| 3 | PZ.21-4/5 | PHASING AND TRAFFIC PLAN: LEVEL 4 & 5 |
| | REPAIR PLANS: | |
| 4 | RP.21-FLR.5N | REPAIR PLAN: LEVEL 5 - FLOOR NORTH END |
| 5 | RP.21-FLR.5S | REPAIR PLAN: LEVEL 5 - FLOOR SOUTH END |
| 6 | RP.21-CLG.4N | REPAIR PLAN: LEVEL 4 - CEILING NORTH END |
| 7 | RP.21-CLG.4S | REPAIR PLAN: LEVEL 4 - CEILING SOUTH END |
| | REPAIR DETAILS: | |
| 8 | RD.21-F1 | FLOOR REPAIR DETAILS I |
| 9 | RD.21-F2 | FLOOR REPAIR DETAILS II |
| 10 | RD.21-F3 | FLOOR REPAIR DETAILS III |
| 11 | RD.21-F4 | FLOOR REPAIR DETAILS IV |
| 12 | RD.21-C1 | CEILING REPAIR DETAILS I |
| 13 | RD.21-C2 | CEILING REPAIR DETAILS II |
| | | |
| | | |



SCALE: 1:100

TS.21-1

SHEET # 1 OF 13

AWS

ADDITIONAL ADJACENT ALTERNATE AMERICAN SOCIETY FOR TESTING AND MATERIALS AMERICAN WELDING SOCIETY

JOINT

POUND(S)

LOW PÒINT

MAXIMUM

MINIMUM

NUMBER

OPENING

PLATE

OPPOSITE

MECHANICAL

MANUFACTURER

NOT TO SCALE

ON-CENTER

PENETRATION

POLYETHYLENE

PROJECTION

REFERENCE

REQUIRED

SCHEDULE

SQUARE FEET

STAINLESS STEEL

TOP AND BOTTOM

TYPICAL AS REQUIRED

TEMPORARY (TEMPERATURE)

UNLESS NOTED OTHERWISE

WATER TO CEMENT RATIO

VERTICAL EACH FACE

WELDED WIRE FABRIC

BUBBLE NUMBER REFERS TO SPECIFIC

REPAIR DETAIL IN THE DETAIL SHEETS

AND/OR REFERS TO SPECIFICATIONS

SECTION 02000 "WORK ITEMS".

WIDE OR WIDTH

SECTION

SIMILAR

SPACES

SQUARE

STANDARD

STORAGE

TIE BEAM

TOOLED JOINT

TOP OF STEEL

TOP OF WALL

TOP OF CONCRETE

THICK

TOP OF

TYPICAL

VERTICAL

MEMBER (MEMBRANE)

PRECAST CONCRETE

POLYVINYL CHLORIDE

PRECAST CONCRETE INSTITUTE

POUNDS PER SQUARE FOOT

POUNDS PER SQUARE INCH

REINFORCEMENT (REINFORCED)

LINEAR FEET

LONG (LENGTH)

KIPS PER SQUARE INCH

K.S.I.

LB.(S)

LG.

L.P.

MAX.

MECH.

MEMB.

NO.

O.C.

P.C.I.

POLY

PROJ.

P.S.F.

P.S.I.

PVC

REINF.

REQ'D

S.F.

SIM.

T&B

THK.

T.O.

T.O.C.

T.O.S.

T.O.W.

V (VERT.)

W.W.F.

LEGEND:

TYP.

N.T.S.

ΑТ @ **BITUMINOUS** BEAM B.O. BOTTOM OF BOT. BOTTOM BRG. BEARING C.F. CUBIC FEET C.I.P. CAST-IN-PLACE CJ CONSTRUCTION JOINT CMU CONCRETE MASONRY UNIT COL.(S) COLUMN(S)

CONC. CONCRETE CONNECTION CONN. CONST. CONSTRUCTION CONT. CONTINUOUS CTR. CENTER DIA. DIAMETER DEMO. **DEMOLISH** DET. DETAIL DIAG. DIAGONAL D.T. DOUBLE TEE DWG.(S) DRAWING(S) DWL.(S DOWEL(S) EA. EACH E.F. EACH FACE E.J. (E/J) EXPANSION JOINT

ELEVATION ELEC. ELECTRICAL EMBED. EMBEDMENT EQ. EQUAL E.W. EACH WAY **EWEF** EACH WAY, EACH FACE EXIST. EXISTING EXP. **EXPANSION** EXT. **EXTERIOR** FIN. **FINISHED**

FLOOR FND. FOUNDATION FOOT (FEET) FTG. GAGE GALLON(S) GALV. GALVANIZED G.C. GENERAL CONTRACTOR GR. GRADE

H.A.S. HEADED ANCHOR STUD HDG HOT DIP GALVANIZED HDP HIGH-DENSITY POLYETHYLENE H.E.F. HORIZONTAL EACH FACE HORIZ HORIZONTAL H.P. HIGH POINT HSS HOLLOW STRUCTURAL SECTIONS INCH(ES)

INFORMATION

INVERTED TEE

INVERTED

SYMBOLS

INFO.

INV.

I.T.

EQUALS GREATER THAN

LESS THAN

GREATER THAN OR EQUAL LESS THAN OR EQUAL

PERCENT

PLUS/MINUS

NUMBER

SPECIFIED 28-DAY DESIGN COMPRESSIVE STRENGTH OF CONCRETE

SPECIFIED YIELD STRENGTH

DIAMETER

REINFORCING BAR SIZE AND SPACING

GENERAL NOTES - PARKING GARAGE REPAIRS:

*CONSTRUCTION DOCUMENTS INCLUDE THE PLANS AND DETAILS ON THE FOLLOWING DRAWINGS AND SEPARATELY BOUND SPECIFICATIONS.

CONSTRUCTION:

- A. CONSTRUCTION SHALL BE IN ACCORDANCE WITH ALL APPLICABLE FEDERAL, STATE OF NEW HAMPSHIRE AND CITY OF MANCHESTER CODES AND ORDINANCES, INCLUDING FIRE CODES.
- ALL DRAIN AND PIPING WORK SHALL CONFORM TO LOCAL BUILDING CODES.
- ALL MATERIAL PROPERTIES SHALL BE AS NOTED IN THE SPECIFICATION.
- COORDINATE ALL UTILITIES SHUTDOWNS WITH OWNER PRIOR TO INTERRUPTING SERVICES.
- CONTRACTOR SHALL CONFORM TO TRAFFIC FLOW COORDINATION AND AREA CLOSURE REQUIREMENTS CONTAINED IN THE CONTRACT DOCUMENTS.
- CONTRACTOR SHALL LIMIT FLOOR LOADING WITHIN THE WORK AREA TO NO MORE THAN 50 PSF. VEHICLE WHEEL LOADS SHALL BE LIMITED TO A MAXIMUM OF 2,000 LBS OVER A 20 SQ. IN. TIRE CONTACT AREA (FLOOR DESIGN LOAD). CONTRACTOR SHALL NOT STORE SUPPLIES OR PARK VEHICLES OVER ANY SHORED AREAS.
- THE CONTRACTOR SHALL VERIFY ALL DIMENSIONS IN THE FIELD.

2. INTENT OF THE REPAIR DRAWINGS:

- A. THE INTENT OF THE STRUCTURAL REPAIR DRAWINGS IS TO SHOW THE EXISTING STRUCTURAL FEATURES AND THE GENERAL LOCATIONS OF REPAIR
- BUBBLE NUMBER REFERS TO SPECIFIC REPAIR DETAIL IN THE DETAIL SHEETS AND/OR WORK ITEM IDENTIFIED IN SECTION 02000 OF THE PROJECT SPECIFICATIONS "WORK ITEMS". NOT ALL ITEMS ARE REPRESENTED WITH A DRAWING DETAIL.
- WHERE WORK ITEM BUBBLE IS NOTED TYP., IT MEANS THE WORK IS TYPICAL THROUGHOUT THE REFERENCED WORK AREA
- WHERE WORK ITEM BUBBLE IS NOTED WITH T.A.R., THE WORK IS TYPICAL AS REQUIRED AND OCCURS AT AREAS IN ADDITION TO THE DESIGNATED LOCATION.
- CONTRACTOR SHALL ESTABLISH EXTENT AND LOCATION OF WORK AND REPAIR AREA AND BE VERIFIED BY THE ENGINEER PRIOR TO COMMENCEMENT OF WORK AT EACH AREA.
- F. REFER TO THE UNIT PRICE BID FORM FOR APPROXIMATED QUANTITIES FOR EACH WORK ITEM, AS APPLICABLE. QUANTITIES MAY VARY AND MAY BE INCREASED, DECREASED OR DELETED AT THE DISCRETION OF THE ENGINEER.

3. CONCRETE:

- A. CONCRETE SHALL HAVE A MINIMUM COMPRESSIVE STRENGTH OF 4,000 PSI (28 DAY) CONFORMING TO NHDOT CLASS AA, AND SHALL BE HIGH EARLY STRENGTH MIX FOR A MINIMUM OF 3,000 PSI IN 5 DAYS. BAGGED MATERIAL MAY BE USED SUBJECT TO PRODUCT DATA, SUBMITTAL TO, AND APPROVAL BY. THE ENGINEER.
- EXPOSED CONCRETE EDGES SHALL HAVE A 1/2" CHAMFER.
- CONCRETE EXPOSED TO VIEW SHALL HAVE SMOOTH FORM FINISH WITH FINS AND FORM MARKS REMOVED TO A SMOOTH, STONE RUBBED SURFACE,
- ALL REINF. SHALL MEET ASTM A615 REQUIREMENTS.
- REINFORCEMENT INTENDED TO BE WELDED SHALL MEET ASTM A706 (REQUIREMENTS FOR WELDABLE REINFORCEMENT).
- AT EXPOSED REINFORCEMENT WHERE CROSS-SECTIONAL LOSSES DUE TO DETERIORATION EXCEED 20 PERCENT, SPLICE WITH REINF. MATCHING EXISTING REINF. BAR SIZE. EXTEND LAP SPLICE REINFORCEMENT BEYOND DETERIORATED SECTION TO DEVELOP PROPER TENSION SPLICE OR, AT ENGINEERS DISCRETION, CONTRACTOR MAY BE DIRECTED TO USE MECHANICAL COUPLERS IN LIEU OF LAP SPLICE.
- ALL EXPOSED REINF. SHALL BE CLEANED BY SAND BLASTING, WIRE SCABBLING TO REMOVE ALL TRACES OF RUST DOWN TO WHITE METAL.
- H. COAT ALL EXPOSED REINF. WITH APPROVED EPOXY COATING.

REMOVAL OF MATERIAL:

- A. ALL MATERIAL REMOVED SHALL BE DONE WITH EXTREME CAUTION.
- B. FOR REMOVAL OF MATERIAL AT AREAS TO BE PATCHED, PROVIDE NEAT SAWCUT TO 1" MAXIMUM DEPTH AT EDGES TO REMAIN.
- NOTIFY ENGINEER IMMEDIATELY OF ANY FIELD CONDITIONS WHICH APPEAR TO DIFFER FROM THOSE SHOWN OR IMPLIED ON THE DRAWINGS.
- RESTORE PRECAST PIECES REQUIRING STRUCTURAL REPAIR.
- PROPERLY DISPOSE OF ALL MATERIALS REMOVED FROM THIS EXISTING STRUCTURE RELATED TO WORK COVERED BY THE CONTRACT DOCUMENTS.

5. PAY ITEMS:

QUANTITIES FOR PAY ITEMS MUST BE VERIFIED BY THE FIELD ENGINEER AND/OR AUTHORIZED REPRESENTATIVE AND CONFIRMED BY THE GENERAL CONTRACTOR PRIOR TO SUBMISSION OF PAYMENT APPLICATIONS.

PHASING AND WORK ZONE CAPTURE NOTES:

- THE PROJECT SHALL BE PERFORMED IN (2) PHASES AS SHOWN ON THE PLANS AND DESCRIBED AS FOLLOWS:
 - PHASE 5S-F / 4S-C (LEVEL 5 SOUTH FLOOR & LEVEL 4 SOUTH CEILING): WORK AREA GENERALLY EXTENDS FROM COLUMN LINE 14.0 SOUTHWARD TO COLUMN LINE 26.
 - PHASE 5N-F / 4N-C (LEVEL 5 NORTH FLOOR & LEVEL 4 NORTH CEILING): WORK AREA GENERALLY EXTENDS FROM COLUMN LINE 14.0 NORTHWARD TO COLUMN LINE 2.
 - THE OWNER (AIRPORT) WILL CLOSE AND CAPTURE THE WORK AREAS ON LEVEL-5 AND LEVEL-4 IN ADVANCE OF THE CONTRACTOR'S WORK IN ACCORDANCE WITH THE PROJECT MILESTONE SCHEDULE.
- THE OWNER WILL PLACE BARRICADES AND SIGNAGE AT THE HELIX ENTRANCES AND PEDESTRIAN ENTRANCES TO THE WORK AREAS. THE CONTRACTOR SHALL GIVE THE OWNER AT LEAST 2 WEEKS ADVANCE WRITTEN NOTICE (WITH EXPLANATION) IF THE MILESTONE SCHEDULE START-DATE OF A PHASE CANNOT BE MET.
- THE OWNER WILL FURNISH AND INSTALL VEHICULAR ACCESS LANE AND PEDESTRIAN WALKWAY TRAFFIC CONTROL DEVICES (BARRELS, ROPING, ETC.) AS ILLUSTRATED ON THE PLANS TO FACILITATE THE PERFORMANCE OF THE WORK. THE CONTRACTOR SHALL COORDINATE HIS WORK WITH THE OWNER TO VERIFY AND MONITOR THE ACCURACY OF SAFETY AREAS PLACEMENT AROUND AND UNDER HIS WORK TO ENSURE THE SAFETY OF THE GENERAL PUBLIC AND PROTECTION OF PARKED PATRON VEHICLES. CONTRACTOR SHALL MAINTAIN AND/OR ADJUST DEVICES TO SUIT THE WORK AREAS DELINEATION AND PUBLIC SAFETY.
- THE OWNER WILL FURNISH AND INSTALL DIRECTIONAL SIGNAGE AS INDICATED ON THE PLANS AND AS REQUIRED FOR PUBLIC USE OF THE FACILITY DURING CONSTRUCTION.
- PUBLIC PEDESTRIAN ACCESS TO THE ELEVATOR LOBBY SHALL BE MAINTAINED AT ALL TIMES. SUB-PHASING OF LOCALIZED WORK AREAS IN FRONT OF THE DOORS WILL BE REQUIRED TO BE PERFORMED BY THE CONTRACTOR.
- THE CONTRACTOR SHALL NOT BEGIN THE WORK IN THE NORTH PHASE AREA UNTIL SPECIFICALLY AUTHORIZED TO DO SO BY THE OWNER. THE WORK IN THE SOUTH PHASE AREA MUST BE COMPLETE AND PREPARED FOR PUBLIC PARKING PRIOR TO RELOCATING THE TRAFFIC CONTROL AND BEGINNING GENERAL WORK IN THE NEXT PHASE AREA
- ISOLATED (UNOCCUPIED) SUB-WORK AREAS (AND SAFETY AREAS) IN THE NEXT PHASE AREA MAY BE CAPTURED BY THE CONTRACTOR, SUBJECT TO THE APPROVAL OF THE OWNER, AND LOCALIZED PREPARATORY WORK INITIATED DURING THE PARKED VEHICLE ATTRITION PERIOD (APPROX. 2 WEEKS) JUST PRIOR TO THE GENERAL CHANGE FROM THE SOUTH PHASE TO THE NORTH PHASE.

WORK ITEM LIST FOR WORK ITEM DEFINITIONS, SEE PROJECT SPECIFICATIONS SECTION 02000

| WORK ITEM | | <u>DESCRIPTION</u> | UNIT | |
|--------------|---|---|------|--|
| 1.0 | GENERAL REQUIREMENTS | | | |
| | 1.1 | GENERAL REQUIREMENTS - MOBILIZATION AND SUPPLEMENTARY GENERAL CONDITIONS* | LS | |
| 2.0 | FLOOR REPAIRS | | | |
| | 2.1 | FLOOR REPAIR — PARTIAL DEPTH AT C.I.P WASH — DRIVE BAYS — 2" DEEP± | SF | |
| | 2.2 | FLOOR REPAIR - PARTIAL DEPTH AT C.I.P WASH - ¾" DEEP± | SF | |
| | 2.3 | FLOOR REPAIR — PARTIAL DEPTH — AT PRECAST CONCRETE FLOOR SLAB — 1" DEEP± | SF | |
| | 2.7A | FLOOR REPAIR - TRAFFIC TOPPING - FULL MEMBRANE SYSTEM* | | |
| | 2.7B | FLOOR REPAIR - TRAFFIC TOPPING - WEARCOAT AND UV-TOPCOAT | SF | |
| | 2.7J | FLOOR REPAIR — TRAFFIC TOPPING AT JOINTLINE PRECAST TEE—TO—TEE FLANGE EDGE JOINTS, NYLON REINFORCED | SF | |
| | 2.8. | FLOOR REPAIR - PENETRATING CONCRETE SEALER WITH MIGRATING CORROSION INHIBITOR (MCI)* | SF | |
| 3.0 | CEILING REPAIRS | | | |
| | 3.3 | CEILING REPAIR - EPOXY CRACK INJECTION | LF | |
| | 3.4 | CEILING REPAIR — OVERHEAD CONCRETE MORTAR REPAIR | SF | |
| | 3.5 | 3.5 CEILING REPAIR — GFRP FABRIC WRAP* | | |
| | 3.6 | CEILING REPAIR - PENETRATING CORROSION INHIBITOR* | | |
| | 3.8 | CEILING REPAIR - GALVANIC CORROSION PROTECTION* | ΕA | |
| | 3.9 | CEILING REPAIR - BLAST CLEANING W/ ABRASIVE MEDIA* | SF | |
| 5.0 | FLOOR SL | AB JOINT REPAIRS | | |
| - | 5.2A | FLOOR SLAB JOINT REPAIR — EXPANSION JOINT NOSING — SURFACE REPAIR | LF | |
| | 5.3 | FLOOR SLAB JOINT REPAIR - REMOVE AND REPLACE FAILED T/T FLANGE JOINT SEALANTS | LF | |
| | 5.5 | FLOOR SLAB JOINT REPAIR-PRECAST TEE ENDJOINT REPLACEMENT-C.I.P. WASH* | LF | |
| 8.0 | BOLLARDS & TRAFFIC CONTROL | | | |
| | 8.1 BOLLARDS & TRAFFIC CONTROL - CONCRETE BOLLARD REMOVAL | | | |
| | 8.2 BOLLARDS & TRAFFIC CONTROL - CONCRETE BOLLARD DISPOSAL* | | LS | |
| | 8.3 BOLLARDS & TRAFFIC CONTROL - PROVIDE TRAFFIC DELINEATOR DEVICES (MATERIAL)* | | EA | |
| | | BOLLARDS & TRAFFIC CONTROL - INSTALL TRAFFIC DELINEATOR DEVICES | ΕA | |
| | 8.4 | Bolling & House Blanch Blanch | | |
| 9.0 | | M ALLOWANCE | | |

*NOT ALL WORK ITEMS ARE REPRESENTED BY A DRAWING DETAIL. REFER TO WORK ITEMS SCOPE AND TECHNICAL SPECIFICATIONS.

UNITS LEGEND:

LS LUMP SUM SF SQUARE FOOT MD MANDAY(8 HR)

LF LINEAR FEET T&M TIME & MATERIAL N/A NOT APPLICABLE

EA EACH ALLOWANCE

SUITE 03101 ZEET, NH 300 AECOM 1155 ELM STI MANCHESTER, (603) 606-48

≡COM

S ITEM WORK

AND


ry of Manchester, New H Manchester - Bost Parking Garage; Level-Ealants, Waterproofing


PROJECT NO: 60638480-T05 CAD DWG FILE: **2_GN.21-1**


DESIGNED BY: JGG DRAWN BY: **JGG** DEPT CHECK: MAB PROJ CHECK: RJD DATE: APRIL 2021


SCALE: N/A GN.21-1


SHEET **2** OF 13














4" THICK PRECAST CONC. TEE FLANGE OR 2" THICK CAST-IN-PLACE CONCRETE WASH -GRIND 1/4" DEEP MIN. PERIMETER GROOVE ---1/2"± || VARIES 6"± DETERIORATED VARIES $3/4"\pm \neg$ TYP. CONC. AREA REMOVE UNSOUND CONCRETE WITH LIGHT ELECTRIC CHIPPING HAMMER OR LIGHT PNEUMATIC SCABBLER OR OTHER APPROPRIATE MEANS. DETERIORATED (SPALLED)
CONCRETE AREA; SIZE VARIES GRIND 1/4" DEEP PERIMETER GROOVE FLOOR REPAIR - PARTIAL DEPTH AT C.I.P WASH - 3/4" DEEP± 2.2 SCALE: $1 \frac{1}{2} = 1'-0''$

VARIES 1" ± DEEP

CONCRETE

- REMOVE UNSOUND

(AVERAGE)

NOTES (ITEM 2.4):

1.) REMOVE DETERIORATED CONCRETE IN REPAIR AREA TO SOUND CONCRETE BY MEANS OF SCABBLING, CHIPPING, HIGH PRESSURE WATER BLAST, AND/OR GRINDING. HAND-HELD PNEUMATIC SCABBLERS OR LIGHT-WEIGHT CHIPPING HAMMERS SHOULD BE USED AND CARE MUST BE TAKEN TO ENSURE CONCRETE REMOVAL DOES NOT CREATE MICRO-CRACKING OR FRACTURES BEYOND THE ORIGINAL DETERIORATED CONCRETE REMOVAL AREA.

2.) GRIND A PERIMETER GROOVE 1/4" DEEP AROUND EXTENTS OF REPAIR AREA ENSURING THAT ALL EDGES ARE ENCOMPASSED BY THE GROOVE. THE PERIMETER GROOVE SHOULD BE CONTINUOUS AND CONSISTANT DEFINING A CONCRETE REPAIR AREA THAT CLOSELY FOLLOWS THE GENERAL SHAPE OF THE DETERIORATION AREA IN A NEAT WORKMANSHIP MANNER WITH A UNIFORM PATTERN AND NO SHARP ANGLES OR CORNERS.

3.) REMOVE REMAINING CONCRETE WITHIN THE PERIMETER GROOVE LINES TO A DEPTH GRADUALLY TAPERING FROM THE 1/4" DEPTH AT THE GROOVE TO THE EXTENTS OF THE SOUND CONCRETE IN THE DEEPEST PART OF THE REPAIR AREA (VARIES UP TO 1"±). EXPOSED AGGREGATE SURFACE WITH A SURFACE PROFILE OF 1/16"± SHOULD REMAIN.

4.) CLEAN ALL EXPOSED REINFORCING STEEL BARS AND CONCRETE SURFACES BY MEANS OF BLAST CLEANING W/ ABRASIVE MEDIA TO NEAR-WHITE METAL SURFACE SSPC-SP10 (SUBSIDIARY) TO REMOVE ALL LOOSE MATERIAL, RUST, AND LATENCE. CONTRACTOR SHALL TAKE CARE TO NOT DAMAGE EXISTING REINFORCING BARS. REINFORCING BARS DAMAGED BY THE CONTRACTOR'S CONSTRUCTION PRACTICES SHALL BE EXPOSED AND SPLICED IN A MANNER AS DIRECTED BY THE ENGINEER AT NO COST TO THE OWNER.

5.) COAT ALL REINFORCING STEEL AND CONCRETE SURFACES WITH THE REPAIR MORTAR MANUFACTURER'S APPROVED BONDING AGENT/PROTECTIVE COATING (EMACO P24 BONDING AGENT, SIKA ARMATEC 110 EPOCEM, OR APPROVED EQIUV.).

6.) INSTALL POLYMER-MODIFIED CEMENTITIOUS REPAIR MORTAR (NEAT) WITH INTEGRAL PENETRATING CORROSION INHIBITOR (EMACO R310-CI AS MFD BY DEGUSSA/MASTER BUILDERS TECHNOLOGIES, SIKATOP 122 PLUS AS MFD. BY SIKA CORP., OR APPROVED EQUIV.) IN ACCORDANCE WITH MFR. INSTRUCTIONS AND BROOM FINISH TO MATCH ADJOINING SURFACES.

NOTES:

- 1. LOCATE AND MARK AREAS FOR REPAIR WITH THE ENGINEER, AND CAPTURE AN ADEQUATE SAFETY AREA ON THE FLOOR LEVEL BELOW THE REPAIR AREA WITH CONSTRUCTION BARRELS AND ROPE.
- 2. REMOVE DETERIORATED CONCRETE OR OLD PATCHING MATERIALS TO SOUND CONCRETE (15-LB CLASS HAMMERS MAX.)
- 3. SAW CUT PERIMETER OF CONCRETE REPAIR AREA IN A NEAT WORKMANSHIP MANNER WITH A UNIFORM PATTERN; REMOVE REMAINING CONCRETE WITHIN SAW CUT LINES.
- 4. CLEAN ALL EXPOSED REINF. BARS AND CONCRETE BY SANDBLAST (SUBSIDIARY). PROVIDE (SUBSIDIARY) SUPPLEMENTARY REINFORCING BARS OR WELDED WIRE FABRIC (WWF) AS REQUIRED BY DETAILS OR AS DIRECTED BY THE ENGINEER.
- 5. COAT ALL REINFORCING AND CONCRETE SURFACES WITH EPOXY BONDING AGENT/PROTECTIVE COATING SUBSIDIARY TO THIS ITEM (MASTER EMACO P 124, SIKA ARMATEC 110 EPOCEM, OR APPROVED EQUAL.)
- 6. APPLY CEMENTITIOUS REPAIR MORTAR IN ACCORDANCE WITH SECTION 03732 CONCRETE REPAIR, AND FINISH TO MATCH ADJOINING SURFACES.

FLOOR REPAIR — PARTIAL DEPTH

AT PRECAST CONCRETE FLOOR SLAB — 1"± DEEP

SCALE: 1 1/2" = 1'-0"

DETERIORATED CONCRETE

AREA (SIZE VARIES)

-SAW CUT PERIMETER

4" THICK PRECAST


1" DEEP

TEE FLANGE

LEGEND

WORK ITEM NUMBER

DETERIORATED CONCRETE REMOVAL



MANCHESTER - BOSTON REGIONAL AIRPORT
ING GARAGE; LEVEL-5 FLOOR & LEVEL-4 CEILING
TS, WATERPROOFING, & MISCELLANEOUS REPAI
FY21-805-31
FLOOR REPAIR DETAILS - II

PROJECT NO: 60638480-T05

CAD DWG FILE: 8-9_RD.21-1&2

DESIGNED BY: JGG

DRAWN BY: JGG

DEPT CHECK: MAB

DATE: APRIL 2021

SCALE: AS NOTED

RD.21-F2

PROJ CHECK: RJD

RD.21-F2SHEET 9 OF 13

3

7

